

CONDENSER STUDIO MICROPHONE

USER'S MANUAL



ENGLISH

EIKON

General

Thank you for buying the EIKON C14 Professional condenser microphone.

The C14 condenser microphone is made following the strictest construction standards which make it the ideal microphone for any professional application.

Equipped with a 1.1"Mylar capsule with gold-coated surface that guarantees a transparent high frequencies response, getting an excellent vocal range and acoustic instruments image even in the most difficult mixing circumstances.

The package includes a shockmount support, anti-pop filter and a sturdy aluminum carrying case.

Features

- Vapor-deposited gold 1,1" diaphragm
- On board bass roll-off filter and -10 db pad
- Very high overload characteristics
- Trasformer coupled FET output stage
- Trasparent sound with superb detail and warm armonic content
- Extended low-frequency range response
- WIMA capacitors
- Integrated shockmount support


EIKON


1

Specifications

Polar Pattern: Uni- Directional Frequency response: 20Hz- 20KhzSensitivity: $-35dB \pm 2 dB (0dB = 1 V Pa , 1 Khz)$ Nominal Impedance: $100 \Omega \pm 20 \%$ (at 1 KHz) Load Impedance: $\geq 1K\Omega$ Self Noise: 14 db-A S/N Ratio: 80 db Max imput Spl: 140 db (at 1 KHz = 1% T.H.D) Filter: High-pass 100Hz 12db/oct Pad: 0 / - 10db Phantom Power Requirement: 48 v Dc Phantom Connector: xlr 3 Pin Weight: 365g Dimensions: H 190 mm x 50 mm Ø Accessories: Shock mount, popscreen

Product complies with CE regulations (F







EIKON

Is a brand of

PROEL S.p.A.

(World Headquarters - Factory)

Via alla Ruenia 37/43

64027 Sant'Omero (Te) – Italy

Tel: +39 0861 81241

Fax: +39 0861 887862

www.eikon-audio.com

